Work Order ID 102065 \*102065\* Page 1 Thursday, May 23, 2013 10:14:47 AM Item ID: Accept \*N900040100\* Setup Start **Revision ID:** Stop Item Name: Decal 5/23/2013 **Start Qty: 12.00 Start Date: Cust Item ID:** Required Date: 5/28/2013 Req'd Qty: 12.00 **Customer:** Reference: Run Date: 13/05/23 Tooling: Approvals: Date: Stop SPC (Y/N): Date: Date: Reject Operation: Turk Accept Qty Qty Work Center and Desci !! . . . a Code Number Stamp true ground Draw Nbr **Revision Nbr** D3976 Α 100 0.00 \*100\* Purchasing 0.00 Memo Purchasing Possible Supplier: Studio Lettrage Material release note is required 110 Receive & Inspect for Damage & Mat'l Certs 0.00 \*110\* 0.00 Packaging Memo

Packaging

NCR: Ye	es / No				<b>WORK ORDER NON-C</b>	CON	<b>IFORM</b>	MANCE / UPE	DATE	·			
										QA Closed:	Dat	te:	
Work Order	:				DISPOSITION	,				EPARTMENT,	_		
Part No					Rework Scrap Use-as-is		ſ	Skid-tube  Machining  noforming	Crosstube Small Fab Finishing		Water Jet d. Eng. Coor. e/Packaging Supplier	Engineering Quality Other	
NCR No	D		·		Work Order Update	<b>.</b>		Large Fab	Composite	J	Supplier		
Root				Descri	ption of work order update	lr	nitial	Acti	ion	Sign &			
Cause	Date	Step	Qty		or Non-conformance	Chi	ef Eng	Descri	iption	Date	Verification	n QC Inspector	
oc/Data												·	
quip/Tooling	_					l							
perator	_												
Material													i
etup	_					Ì							
Other	_												
rocess	_												
Supplier	_	, ·											
raining													
Inapproved			<u> </u>	L		<u> </u>	:	L				31.	4
<u>`</u>		;			<del></del>	AUL	CATE	GORY		_ <u></u>			_
Landing		`¥	्रे श्रेत	7 <del>5</del> 4	General	,t		美洲 翻	James Marie	•	•,;	<u> </u>	
L	Bending				Bend	$\vdash$	Grain		<u> </u> _	Ovalized		Pressure/Forced	
<u> </u>	Centre No	ot Conce	ntric to	o/s	BOM/Route		Hardwa		ļ_	Over/Under	<b>-</b>	Temperature/Cure	
	Cracks			<u> </u>	Broken/Damaged	$\overline{}$	•	ion Incomplete	<u> </u>	Part Incorred	<b>-</b>	Weld	
	Crushed/	Crimped		ļ	Burrs	$\vdash$		ions Incomplete/U	Jnclear	Part Lost/Mi	ssing [	Wrong Stock Pulled	
1_	Cuffs			<u> </u>	Contamination	-	Mainte		<b> </b> _	Part Moved			
	Heat Trea	it			Countersink	Ц	Mislabe	eled	<u> </u> _	Positioned W		<del></del>	
	Inspection	n Strip in	Tube	· <u>L</u>	Cut Too Short	-	Misread	d	L.	Power Loss/S	Surge	Other	_
	Ripples in Bend Drill Holes		=	$\vdash$	Offset			:	***		_		
L	Torque Waves in Extrusion Drawing		Drawing	$\vdash$		Calibration				·	_		
	Turning Sequence Finish		-		Sequence					_			
	Wave/Twist in Tube				Folio		Outside	Dimensions					

DQA:

Date:

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Work Orde Thursday, May 2				*10	2065*				Page 2
Item ID: Revision ID: Item Name:	D3976-3			Accept	*N900	0040100	<b>)*</b> Se	tup Start	*NS1* *NS2*
Start Date: Required Date: Reference:	5/23/2013	Start Qty: 12.00 Req'd Qty: 12.00	*12* *12*		Cust Item Customer:			·	
Approvals:		an:		Tooling: SPC (Y/N):		ate:	Ru	in Start Stop	*NR1* *NR2*
Sequence ID/ Work Center II 120 *120* QC Quality Control	)	Operation Description QC5- Inspect part compl	eteness to step on W/O	Set Up/ Run Hours 0.00 As 0.00 73.5	Teol ID	Tool # Plan Code	Accept Qty	•	Reject Insp. Number Stemp
*130 *130* Packaging Packaging		Identify as per dwg & Sto	ock Location:	0.00	ST377	h	12 X	MLO	13/05/27
140 * <b>14\O</b> *		QC21- Final Inspection -	Work Order Release	0.00				13/	6/28 8

Quality Control

MCJ 13-05-28

NCR.	Vec	1	No	

DQA: \_\_\_\_\_ Date: \_\_\_\_\_

NCR: Ye	es / No				WORK ORDER NON-	CONFOR	MANCE / UP	DATE	QA Closed:	Dat	e:
Work Orde	<del>``</del>				DISPOSITION			AGAINST DE	PARTMENT	/PROCESS	
Part No	o				Rework Scrap Use-as-is Work Order Update	Ther	Skid-tube Crosstube Machining Small Fab Thermoforming Finishing Large Fab Composite		Prod. Eng. Coor. Rec/Store/Packaging		Engineering Quality Other
Root				Descri	ption of work order update	Initial	Ac	ction	Sign &		
Cause	Date	Step	Qty		or Non-conformance	Chief Eng	1	cription	Date	Verification	QC Inspector
Ooc/Data						1					
quip/Tooling											
Operator											
/laterial											
etup									1		
Other											
rocess											
upplier											
raining											
Inapproved		<u> </u>					1				
			•		F	AULT CAT	GORY				
Landin	g Gear			_	General			_	٦	-	_
L	Bending				Bend	Grain		<u> </u>	Ovalized	Ļ	Pressure/Forced
	Centre No	ot Concei	ntric to (	o/s	BOM/Route	Hardw	are		Over/Under	<b>⊢</b>	Temperature/Cure
	Cracks			L	Broken/Damaged	<del></del>	tion Incomplete	_	Part Incorred	<b>⊢</b>	Weld
1	Crushed/	Crimped			Burrs	$\blacksquare$	tions Incomplete	/Unclear	Part Lost/Mi	ssing [	Wrong Stock Pulled
	Cuffs			<u> </u>	Contamination	Maint	enance	_	Part Moved		
	Heat Treat Countersink		Mislab		<u>_</u>	Positioned V	· · ·				
	Inspectio	n Strip in	Tube		Cut Too Short	Misrea	ad		Power Loss/	Surge	Other
	Ripples in Bend Drill Holes			Offset							
	Torque Waves in Extrusion Drawing		Drawing	Out of	Calibration			-			
	Turning Sequence Finish		Out of	Sequence							
	Wave/Twist in Tube		Folio	Outsid	Outside Dimensions						

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

**Picklist Print** 

Thursday, May 23, 2013 10:14:46 AM

Page 1

Work Order ID:

102065

Parent Item:

D3976-3

Parent Item Name:

Decal

**Start Date:** 5/23/2013

Required Date: 5/28/2013

**Start Qty: 12.00** 

Required Qty: 12.00

**Comments:** 


Component Item ID/ Item Name	Replacement Item ID	Mfg/ Purch	Bin Item	Primary Location	Last Location	Route Seq ID	Unit of Measure	Qty on Hand	Qty per Kit	Total Qty	Qty Issued	Date Issued	Status
D3976-3P		Purchased	No			110	Each	0.0000	1	$\sim 12$	$\sim$ (2)		77
Decal										217	SV 13	シンシュ	ノナ

21 J-3-3-1

			DQA:	: D	Date:
			•		
NCR.	Vec /	No	WORK ORDER NON-CONFORMANCE / UPDATE		

											QA Closed:	Date	<u>:</u>
Work Orde	ori.					DISPOSITION				AGAINST DE	PARTMENT	/PROCESS	
Part N	- - No					Rework Scrap Use-as-is Work Order Update	] ] ]	Skid-tube Crosstube  Machining Small Fab  Thermoforming Finishing  Large Fab Composite			4	Water Jet d. Eng. Coor. re/Packaging Supplier	Engineering Quality Other
Root	Т				Descri	ption of work order update	Initi	al	Acti	ion	Sign &		
Cause		Date	Step	Qty		or Non-conformance	Chief	Eng	Descr	iption	Date	Verification	QC Inspector
Doc/Data													
Equip/Tooling							]						[
Operator							1						
Material							1						
Setup													
Other							-						
Process													
Supplier													
Training			]										
Unapproved													_1
•					317.		AULT C	ATE	GORY				
Landi					ാത്	General		,	*:	<u></u>	1	г	
		Bending			· _	Bend ,	$\vdash$	ain	4	<u> </u>	Ovalized	· .	Pressure/Forced
	-	Centre No	ot Concer	ntric to	o/s	BOM/Route	$\vdash$	rdwa		_	Over/Under	_	Temperature/Cure
	-	Cracks				Broken/Damaged	_	•	ion Incomplete	—	Part Incorre	<b>├</b>	Weld
	_	Crushed/	Crimped		<u> </u>	Burrs			ions Incomplete/U	Inclear	Part Lost/Mi	issing _	Wrong Stock Pulled
	$\vdash$	Cuffs			<u> </u>	Contamination	$\vdash$		enance	-	Part Moved	Managa	
	-	Heat Trea			<u> </u>	Countersink	<del>     </del>	slabe		·	Positioned V Power Loss/		Other
	-	Inspectio		rube	<u> </u>	Cut Too Short	$\vdash$	sread	ג	L	Jeomet ross/	onike [	Comer
	Ripples in Bend Drill Holes			$\vdash$	fset	Calibration				·			
	Torque Waves in Extrusion Drawing			$\vdash$									
		_	Turning Sequence Finish  Wave/Twist in Tube Folio			<del></del>		Sequence Dimensions					
i	1 I'	wave/Iw	ist in Tut	e e		Folio	I lor	irsine	: Dimensions				

2.00 DART AEROSPACE USA, INC STEP ACTUATOR 1.25 0.050 P/N 41232-200-001-001 TYP STC SR09400RC FAA/PMA D3976-1 DECAL



LX13/05/23 W10:102065

D

С

NOTES:
1) MATERIAL: 220 SCOTCHCAL FILM, BY 3M

RED LETTERS & MARKINGS ON WHITE BACKGROUND REF CROSS REFERENCE Era DRAWING 41232-200-008

2) FINISH: N/A

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: N/A

6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3976-X"

7) WEIGHT: 0.01< LBS

A NEW ISSUE 09.07.09 REV. DESCRIPTION BY DATE DART AEROSPACE USA, INC DESIGN DRAWN CHECKED DRAWING NO. REV. A MFG. APPR. D3976 SHEET 1 OF 1 APPROVED TITLE SCALE DE APPR. DECAL - STEP ACTUATOR NTS COPYRIGHT © 2009 BY DART AEROSPACE USA, INC JENNI IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION E USED FOR MAY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON. DATE 09.07.09

										DQA:	Date	:
NCR: Y	es / No				WORK ORDER NON	-COI	VFORM	MANCE / UP	DATE	QA Closed:	Date	:
Work Orde	r:				DISPOSITION				AGAINST DI	EPARTMENT	/PROCESS	
Part N NCR N	0				Rework Scrap Use-as-is Work Order Update		Machining Small Fab Thermoforming Finishing		Crosstube Small Fab Finishing Composite	Water Jet Prod. Eng. Coor. Rec/Store/Packaging Supplier		Engineering Quality Other
Root				Desci	ription of work order update		nitial	Act	tion	Sign &		
Cause	Date	Step	Qty		or Non-conformance	Ch	ief Eng	Desc	ription	Date	Verification	QC Inspector
oc/Data quip/Tooling Operator Material detup Other Process dupplier Training Unapproved												
· · · · · · · · · · · · · · · · · · ·						FAUL	T CATE	GORY				
Landin	Bending Centre Not Concentric to O/S Cracks Crushed/Crimped Cuffs Heat Treat Inspection Strip in Tube Ripples in Bend Torque Waves in Extrusion			General  Bend  BOM/Route  Broken/Damaged  Burrs  Contamination  Countersink  Cut Too Short  Drill Holes  Drawing		Instruct Mainte Mislabe Misread Offset	on Incomplete ions Incomplete/ nance led	Unclear	Ovalized Over/Under Part Incorred Part Lost/Mi Part Moved Positioned V Power Loss/	ct issing Vrong	Pressure/Forced Temperature/Cure Weld Wrong Stock Pulled Other	
ľ	Turning Sequence				Finish		Out of s	Seguence				

Outside Dimensions

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Wave/Twist in Tube

Folio

# Studio de Lettrage

210 Main Street W Hawkesbury, Ontario K6A 2H6

# INVOICE

Invoice No.:

20157

Date:

05/27/2013

Ship Date:

Page:

Re: Órđer No.

WO10025

Sold to:

**Dart Aerospace Ltd** 

1270 Aberdeen Hawkesbury, Ontario K6A 1K7

Ship to:

Dart Aerospace Ltd

Hawkesbury, Ontario

Business No.:	82500 7651 RT	0001	/ £ yy			
Item No.	Unit	Quantity /	Description	Тах	Unit Price	Amount
		12	3M STICKERS D3976-3P PO#19973	Н	6.25	75.00
			H - HST 13% HST			9.75
					GP12	527
	and page section.					
Studio de Lattraca	HST: #8250076511	T0001				
Shipped By:	Tracking !					
Comment:					. Total Amoun	<b>t</b> 84.7
Sold By:					and the state of t	<b>2</b>

****Certificate of Conformity**** Customer:					
<del>Oustomer.</del>	Audio h	etteage			
Purchase Order #:	Packing Slip #:	Part#: 	Serial #:		
Description:	10025	Quantity:	<u> </u>		
Shic	KER	12			
Certification:					
We hereby certify tha	t:				
The above the lister accordance with a	ed items were manufac pplicable drawings and	ctured, repaired and/ I/or specifications;	or inspected in		
accordance with applicable drawings and/or specifications;  2. All work was accomplished in accordance with the Dart Aerospace					
2. All work was acco	mplished in accordanc	e with the Dart Aeros	paco		
All work was acco     Purchase Order;	mplished in accordanc	e with the Dart Aeros	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Purchase Order;  3. Results of all inspe	ections, chemical or ph	ysical tests, as well	as other evidence		
Purchase Order;  3. Results of all inspound which shows the action is the second secon		ysical tests, as well erials, parts and/or a	as other evidence		
Purchase Order;  3. Results of all inspound which shows the action is the second secon	ections, chemical or ph cceptability of raw mate	ysical tests, as well erials, parts and/or a	as other evidence		
Purchase Order;  3. Results of all insponder shows the accomponents are or	ections, chemical or ph cceptability of raw mate	ysical tests, as well erials, parts and/or a	as other evidence		
Purchase Order;  3. Results of all inspound which shows the action is the second secon	ections, chemical or ph cceptability of raw mate	ysical tests, as well erials, parts and/or a	as other evidence		
Purchase Order;  3. Results of all insponder shows the accomponents are or	ections, chemical or ph cceptability of raw mate	ysical tests, as well erials, parts and/or a	as other evidence		
Purchase Order;  3. Results of all inspendence which shows the accomponents are or authority:	ections, chemical or phoceptability of raw matern file and available for i	nysical tests, as well a erials, parts and/or a nspection at any time	as other evidence		
Purchase Order;  3. Results of all inspendence which shows the accomponents are or authority:	ections, chemical or ph cceptability of raw mate	nysical tests, as well a erials, parts and/or a nspection at any time	as other evidence		
Purchase Order;  3. Results of all inspendence which shows the accomponents are or authority:	ections, chemical or phoceptability of raw matern file and available for i	nysical tests, as well a erials, parts and/or a nspection at any time	as other evidence		



## **Product & Instruction Bulletin 8522**

Release I, Effective September 2008 See Bulletin Change Summary and end of Bulletin This Bulletin now includes Instruction Bulletin 4.23

# Scotchcal<sup>™</sup> Changeable Opaque Imaging Media

8522

# **Product Description**

# **Recommended Types of Graphics and End Uses**

#### For Thermal Inkjet Printing

This durable, 7 mil, opaque, changeable film is optimized for use with selected thermal inkjet printers and inks. Ink dries quickly on the film. When overlaminated, it is warranted for medium term, outdoor weatherable graphics, and long term indoor graphics.

When constructed and used as described in this Bulletin, these types of graphics and end uses may be warranted by the 3M ™ MCS ™ Warranty. Please read the entire Bulletin for details.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
  - Graphics for vans, personal vehicles, trucks and buses
  - Novelty posters
  - Retail and point-of-purchase displays
  - Information graphics such as maps and directories
  - Entertainment promotions in museums, zoos, parks, theatres, sports venues
  - Education and presentation graphics
  - Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications

#### **Limitations of End Uses**

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs or recommend other products.

# Unsuitable End Uses for This Product

- Not for electronically cut individual letters and numbers
- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallboard
- Applications subjected to gasoline vapors or spills
- · Application to corrugated or highly irregular surfaces or sharply raised areas
- · Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.
- Graphics made for automotive Original Equipment Manufacturers (OEM); contact 3M Automotive Division at 1-800-328-1684 for alternatives.

#### **About Water-Based Inkjet Technology**

Standard inkjet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication, Shelf Life and Storage sections in this Bulletin. Staying in the middle of these ranges always provides optimum performance.

## **Compatible Products**

#### **3M Graphic Materials**

For complete details about graphic construction options, recommended uses and durability, refer to the Product Bulletin for the base film or substrate (media) you are using. See **3M**Related Literature at the end of this Bulletin.

This Bulletin provides details about the base film and construction options and warranty. Additional specific information about compatible products can be found in the Product and Instruction Bulletins listed in **3M Related Literature** at the end of this bulletin.

#### **3M Graphic Materials**

For complete details about graphic construction options, recommended uses and durability, refer to the Product Bulletin for the base film or substrate (media) you are using. See **3M Related Literature** at the end of this Bulletin.

#### Film

3M™ Scotchcal™ Opaque Imaging Media 8522

#### Overlaminate

- 3M™ Scotchcal™ Luster Overlaminate 8519
- 3M ™ Scotchcal ™ Matte Overlaminate 8520

#### **Printers and Inks**

HP Designjet Printers	HP Inks
<ul> <li>2500CP and 2000CP</li> <li>2800CP and 3800CP</li> <li>3500CP and 3000CP</li> <li>HP Designjet 5000 and 5500</li> </ul>	<ul> <li>Designjet CP Ink System UV (pigment-based)</li> <li>Designjet CP Inkjet System (imaging ink)</li> </ul>
• Z6100	HP 91 Vivera Ink System

Epson Printers	Epson Inks
Stylus Pro 9500	Archival Inks
<ul> <li>Stylus Pro 10000 printer</li> </ul>	
<ul> <li>Stylus Pro 10600 printer</li> </ul>	

#### **Characteristics**

These are typical values for unprocessed product; processing may change the values. Contact your 3M representative for a custom specification.

Characteristic	Description				
Media	7 mil, white, opaque graphic film				
Liner	Low-slippage, lay flat paper				
Adhesive	Changeable, pressure sensitive .				
Thickness	Media with adhesive: 7.5 to 8 mil (nominal)				
Warranted application substrates	See next page.				
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)				
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)				
Removable	For up to one year; see Warranty Information				

Characteristic	Description					
Warranted application substrates	Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.					
	Alodine (anodized aluminum)					
	Automotive panels (automotive painted steel)					
	Fruehauf (painted aluminum)					
	FRP (fiberglass reinforced plywood)					
	• Glass					
* *	Imron ® (polyurethane-painted metal panel)					
	Acrylic					
	Sintra ™ board					
	Note: Use on any other substrate is strictly on a graphics manufacturer and customer test and approve basis. Test for both adhesion and removal characteristics. The plasticizer in some banner materials may migrate. This may cause the edge of the graphic to peel or lift off of the banner. For optimum performance, follow the guidelines in the section, Creating A Laminated Overlap, on page 4.					

# **Warranty Information**

The warranty given in the Product Bulletin that is current at the time you purchased the film is the one that 3M will honor. The warranties in the following table(s), given in years, are for finished graphics exposed in a vertical exposure in the United States except the Desert Southwest. See the warranty sections following this table for additional information.

# **3M<sup>™</sup> MCS<sup>™</sup> Warranty** Durability for Finished Graphics

Construction (film and	HP Printers & Inks		Epson Printers & Inks		Removal
overlaminate on warranted substrate	Outdoor	Indoor	Outdoor	Indoor	
8522/8519	3 years	5 years	2 years	5 years	1 year without
8522/8520					chemical strippers or tools

#### **Warranty and Limited Remedy**


The following is made in lieu of all other express or implied warranties, including any implied warranty of **merchantability** or fitness for a particular purpose or implied warranty arising out of a course of dealing, custom or usage of trade: all 3M products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in this Product Bulletin. 3M will replace or refund the price of any 3M materials that do not meet this warranty within the specified time periods. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor or non-3M materials charges.

See the Graphics Market Center Warranty Brochure, which gives the terms, additional limitations of the warranty, if any, and limitations of liability.

# Graphic Construction Options

#### **Opaque Graphics**

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.



#### **Fabrication**

Different combinations of shop temperature and humidity can affect the handling of the media, the protective finish and the printed graphic. For optimum performance, use the *middle* of each of these ranges whenever possible.

**Shop Temperature** 

Acceptable: 60° to 95°F (15° to 35°C) Optimum: 65° to 73°F (18° to 23°C)

Shop Humidity

Acceptable: 20% to 80% Optimum: 45% to 60%

Condition the Media Before Use

These steps are especially important if you are operating outside the conditions recommended under Fabrication, above.

- Leave the media in its original packaging until you are ready to condition and use it.
- The day before you need it, remove the media from the box and remove the plastic.
- Condition the media for 24 hours in the same environment as the printer.

# Printer Settings for Optimum Quality

Refer to your Hewlett Packard printer manual for detailed operating instructions.

The quality of a printed image depends on a combination of factors: correct media selection, printing software and raster imaging processor (RIP), shop conditions, etc.

The printers qualified to use this media have print mode options that are programmed specifically for these media. Current charts that show the various modes and printing dpi, and the quality results you can expect are available at www.hp.com under the website's support section. We recommend that you print the same image at all of these settings to determine acceptable print and productivity results.

The highest quality settings are usually desirable for backlit applications.

The correct media selection makes most other necessary adjustments to the printer.

- For the HP DesignJet CP 2000 or 3000 series printers, select the Opaque Vinyl UV setting.
- For the HP Designjet 5000 series printers, select the **3M Changeable UV** setting or the HP **Durable Gloss UV** or HP **Colorfast Viny!** setting.
- For the Z series printers, refer to HP's website or printer manuals.

Note: The HP printer settings lay down less ink per pass, which results in better ink absorption and quicker drying times.

- For the HP DesignJet CP 2000 or 3000 series printers, select the Opaque Vinyl UV setting.
- For the HP Designjet 5000 series printers, select the 3M Changeable UV setting or the HP Durable Gloss UV or HP Colorfast Vinyl setting.
- For the Z series printers, refer to HP's website or printer manuals.

Note: The HP printer settings lay down less ink per pass, which results in better ink absorption and quicker drying times.

## **Drying Guidelines**

Usually, the media can be laminated within 10 minutes after printing. However, especially in high humidity conditions, we recommend waiting 15 to 30 minutes before laminating.


Use care when handling graphics that have not been laminated to avoid scratching and abrasion.

Graphics made with this media and ink combination typically may be wound directly on a take-up roll after printing.

Whether or not you want a warranted graphic, an overlaminate is recommended to enhance durability, especially in outdoor applications.

#### **Overlaminate**

FIGURE 1
Typical Laminator Thread-up



#### Creating a Laminated Overlap

Creating a laminated overlap helps ensure that the graphic does not peel or lift away from certain banner materials that may be subject to plasticizer migration. This method may also be used for flat, rigid or flexible sign applications.

- 1. Print the graphic as usual.
- 2. On all sides of the graphic, score *the film only* to the correct, final graphic dimension *without cutting through the liner*.

Weed away the excess film, leaving the bare liner exposed around the graphic. See FIGURE 2.

FIGURE 2 Trim and Weed Film Margin Only







Weed Margin

3. Laminate the graphic as usual (see page 5), making sure that at least one inch of the bare liner is covered by the laminate. See FIGURE 3.



Dart Aerospace Ltd. 1270 Aberdeen Street Hawkesbury, ON K6A 1K7

Tel: 613 632 9577 Fax: 613 632 1053

#### PURCHASE ORDER

#### Purchase Order ID PO19973

Purchase Order Date 5/23/2013 PO Print Date 5/23/2013

Page Number 1 of 1

Order From:

VC-STU001

STUDIO DE LETTRAGE 2001 210 MAIN WEST HAWKESBURY, ON K6A 2H6

CA

**Contact Name** 

Vendor Phone

613 632 5449

Vendor Fax

613 632 9491

Vendor Account Nbr

Buyer

Brigitte Golden

Requisition Nbr

Tax Resale Nbr

10127-2607

Terms Currency Net 30 CAD

FOB

Destination-Collect

Ship To:

DART AEROSPACE LTD

1270 ABERDEEN

HAWKESBURY, ON K6A 1K7

**CANADA** 

Line Nbr Reference Revision ID

Vendor Part Number

ference Description/
vision ID Mfg ID

Req Date/

eq Date/ Req Qty/
Taxable Unit of Measure/

Ship Method Unit Price

Extended

Price

D3976-3P

Decal

5/27/2013

Yes

12.00

Each

Yours ppd

\$6.2500

\$75.00

Special Inst:

Aas per DWG: D3976 Rev: A

B102065

PO Total:

\$75.00

È.,

()

M

No substitution or deviation without consent.

Certificate of Conformity or Material Certification required - YES NO